WATERLESS ENGINE CLEANER

Technical Data Sheet (TDS)

Areas of Use

- Its foam is controlled. Can be used at any water temperature.
- Active ingredients may be biodegradable. It is suitable for all vehicle anda paint types.
- It is formulated to suit every water hardness.
- It is economical, saving energy and time.

Directions for Use

- According to preference, it is applied to the engine by diluting with 1/2 or 1/3 water. Wait for 5 minutes to 10 minutes after application to the vehicle engine. Afterwards, with a minimum of 6 bar air, the dirt and oil residues on the surface are removed from the engine surface. It is dried with a clean cloth.

AUTO CHER OTO BAKIM LİMİTED ŞİRKETİ · İçerenköy, Çetinkaya Sk. No:17, 34752 Ataşehir / Istanbul, Türkiye
Tel: +90 216 575 00 84 · Mobile / WhatsApp: +90 533 818 42 32 · info@autocher.com.tr · autocher.com.tr

Physical and Chemical Properties

Physical state	**Liquid**
Odor	**Characteristic**
pH	**10-11**
Melting point / Freezing point	**Not applicable**
Boiling point / Boiling interval	**Not applicable**
Flashing Point	**Not applicable**
Evaporation rate	**Not applicable**
Flammability	**Not flammable**
Upper/lower limits for flammability or explosion	**Not applicable**
Steam Pressure	**Not applicable**
Steam density	**Not applicable**
Relative Density	**1,0265 gr / ml**
Solubility in water	**Fully soluble**
Log Pow (log octanol/water partition coefficient)	**Not applicable**
Flammability temperature	**Not applicable**
Decay temperature	**Not applicable**
Fluidity	**Not applicable**
Explosive / oxidizing property	**Not applicable**
Viscosity	**Not applicable**

Consumer Information

Hazard Statements (H)

- H318 Causes serious eye damage.

Precautionary Statements (P)

- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P280 Wear eye protection / face protection.
- P310 Immediately call a POISON CENTER / doctor